

BUILT IN ICE DISPENSER

For ready chilled Drinks



FEATURES

- Customizable aesthetics
- Led lighting
- Removable drip tray
- Ice drawers: 400 g/ cad
- Total Ice drawer: 800 g
- Ice cycle: every 10 minutes
- Ice production: 18 Kg/24h cad
- Total Ice production: 36 Kg/24h
- Ambient operating temperature: 15°C - 25°C



FUNCTIONING

- Fully integrated ice dispenser
- Automatic stop when ice full

SAFETY AND CONVENIENCE

- Water missing warning
- All front components can be pulled out and washed
- Energy saving mode



TECHNICAL AND CONSUMPTION

- Material: stainless steel 304 and glass
- Outside dimensions: H 455xW 595xD 380 mm
- Built in dimensions: H 450xW 560xD 560 mm
- Appliance weight: 26 Kg
- Package dimensions: H 550xW 700xD 455 mm
- Gross weight: max 32 Kg
- Standard connection cable: schuko plug
- Refrigerant gas: R134A - 85g
- Noise Level: <40 dBA
- Rated electrical power: 0,06 kW - 0,3 A
- Voltage: 220-240V / 50/60Hz
- Voltage: 110V/60 Hz on request
- Energy consumption in a year: <180 kW/h (A++)
- Approvals: CE - CB- GMARK - EMC - SGS

ACCESSORIES SUPPLIED

- Ice scoop and glass
- Drip tray
- User manual and notes
- Power connection cable
- Fixing screws



PRO
KUCH

MACCHINA DEL GHIACCIO DA INCASSO



CARATTERISTICHE

- Estetica personalizzabile
- Illuminazione Led
- Griglia removibile
- Cassetto del ghiaccio: 400 g
- Ciclo del ghiaccio: ogni 10 minuti circa
- Produzione ghiaccio: 18 Kg/24h cad
- produzione ghiaccio totale: 36 Kg/24h
- Temperatura d'ambiente consigliata: 15°C - 25°C

FUNZIONAMENTO

- Dispenser ghiaccio integrato
- Blocco automatico del ghiaccio a cassetto pieno

SICUREZZA

- Allarme mancanza acqua
- Tutti i componenti a vista sono facilmente lavabili
- Modalità risparmio energetico



DATI TECNICI

- Materiale: acciaio inox 304 e vetro
- Dimensioni esterne: H 458xW 595xD 380 mm
- Dimensioni incasso: H 450xW 560xD 560 mm
- Peso netto: 26 Kg
- Dimensione imballo: H 550xW 700xD 455 mm
- Peso lordo: max 32 Kg
- Cavo di connessione standard: schuko
- Gas refrigerante: R134A - 85g
- Livello di rumore: < 40 dBA
- Potenza: 0,06 kW - 0,3 A
- Voltaggio: 220-240V / 50/60Hz
- Voltaggio: 110V/60 Hz su richiesta
- Consumo annuo: < 180 kW/h (A++)
- Approvazioni: CE - CB- GMARK - EMC - SGS

ACCESSORI

- Griglia
- Paletta e bicchiere per ghiaccio
- Manuale d'uso e istruzioni
- Cavo di connessione
- Viti di fissaggio

